

SUBMITTAL SHEET

Irrigation Fittings **Sprint**

Sprint fittings are push to connect fittings for Polyethylene pipe in irrigation applications. They are removeable and reusable, making installation very easy.

Sprint Features:

- 100% corrosion resistant
- Push to connect solution without special tools
- Install regardless of temperature or weather
- Approved for burial
- Removeable and reusable
- 5-year warranty

Sprint Specifications:

- For use with 100 psi Polyethylene (PE) pipe
- Working pressure: up to 230 psi (16 bar)
- Temperature: -4° F to 104° F
- Made from glass-fiber reinforced PA

Sprint Installation:

Squarely cut PE pipe to desired length. Mark pipe depth using guide on packaging. Insert pipe into fitting with a twisting motion. Check connections after installation.

To remove, open the sleeve by using a wrench and turn the cap counter clockwise. Remove the pipe. Remove the fitting components from pipe and reassemble fitting.

Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	



IRRIGATION



Sprint Couplings						
Part Number	Description	H	W	D	Wt (lbs)	
SPRC34	3/4 in.	4.00	1.75	1.75	0.24	



Sprint Elbows						
Part Number	Description	H	W	D	Wt (lbs)	
SPRE34	3/4 in.	3.50	1.75	3.50	0.28	



Sprint Male Adapters						
Part Number	Description	H	W	D	Wt (lbs)	
SPRMA34	3/4 in.	2.75	1.75	1.75	0.13	



Sprint Tees						
Part Number	Description	H	W	D	Wt (lbs)	
SPRT34	3/4 in.	5.38	1.75	3.50	0.41	



Sprint Caps						
Part Number	Description	H	W	D	Wt (lbs)	
SPRCAP34	3/4 in.	2.06	1.75	1.75	0.13	